

Wildman, Harrold, Allen & Dixon

Page 1 of 1

Wildman, Harrold, Allen & Dixon LLP

225 West Wacker Drive
Chicago, Illinois 60606-1229
312-201-2000
312-201-2555 fax
www.wildmanharrold.com

**RECEIVED
CENTRAL FAX CENTER****OCT 03 2006**

Facsimile Cover Sheet

**Wildman Harrold**

Attorneys and Counselors

Date: Tuesday, October 03, 2006 2:41:52 PM**From:** Keating, Diane**CC:****Transmitting to:** K. Cyrus Kianni**Client No.:** B4331 00001**Total Pages:** 02 including cover sheet**Phone:****Company:****Company Phone:****Company Fax:** 1-571-273-8300**Subject/Notes:** 10/735,016

If you do not receive all transmitted pages, please contact our Fax Department at (312) 201-2498

This facsimile is intended only for the use of the addressee named above, and may contain legally privileged and confidential information. If you are not the intended recipient of this facsimile, you are hereby notified that dissemination, distribution or copying of this facsimile is strictly prohibited. If you have received this facsimile in error please notify our fax department by telephone at (312) 201-2498. If long distance, please call collect and please return the original of this facsimile to the attention at the above address via the U.S. Postal Service. Unless expressly stated otherwise, any tax advice in this message is not intended or written to be used, and cannot be used by a taxpayer, for the purpose of avoiding penalties that may be imposed on the taxpayer. Please consult your tax attorney regarding the form of tax advice that may be relied upon to avoid penalties under the Internal Revenue Code.

OCT 03 2006

Draft Proposed Claims

1. A method for avoiding saturation of an opto-electrical receiver, the method comprising:

manufacturing an end surface of a fiber optic device at a pre-determined acute angle other than 45 degrees from a side of the fiber in order to avoid saturation of said opto-electronic receiver;

transmitting light into the fiber core of the optical fiber; and

attenuating the light by reflecting the light off the angled polished end surface in order to avoid saturation of said opto-electronic receiver receiving the light.

2. The method of claim 1 wherein said step of manufacturing said end surface is accomplished by polishing said end surface to said pre-determined acute angle.

3. The method of claim 1 wherein said fiber optic device further comprises an optical fiber, and a fiber core within the optical fiber comprising a fiber core cladding interface, wherein said angled end surface is on an end of said optical fiber.

4. The method of claim 1 further comprising providing an active device operationally coupled to the optical fiber, and emitting said light from the active device.

5. The method of claim 4 wherein the active device is a vertical cavity surface emitting laser.

6. The method of claim 4 wherein the active device is a light emitting diode.

7. The method of claim 1 wherein the acute angle is in a range substantially between at least one of 39-44 degrees and 46-51 degrees.

8. A method for avoiding saturation of an opto-electrical receiver, the method comprising:

manufacturing a fiber optic device comprising an optical fiber, a fiber core within the optical fiber comprising a fiber core cladding interface, and an angled polished end surface on an end of the optical fiber, wherein the angled polished end surface is manufactured to be at a pre-determined acute angle other than 45 degrees from a side of the fiber in order to avoid saturation of said opto-electronic receiver;

transmitting light into the fiber core of the optical fiber; and

attenuating the light by reflecting the light off the angled polished end surface in order to avoid saturation of said opto-electronic receiver receiving the light.